

SPECIFICATION SHEET

Multi-Stage Brackish (MSB) Pump

MODEL MSB-120*

for Reverse Osmosis Desalination

HYDRAULIC DESIGN	
PUMP	Horizontal multi-stage centrifugal pump with barrel flanged joint construction.

OPERATING PARAMETERS	
LIQUID	Brackish water
OPERATING TEMPERATURE	0.6 - 70.0° C
MAXIMUM STORAGE TEMPERATURE	85° C
PUMP OPERATING FLOW RANGE*	60-132 m ³ /h
MAXIMUM PRESSURE	35 bar
FILTRATION REQUIREMENT	20 microns

*Range may vary.

PERFORMANCE	
PEAK EFFICIENCY	Up to 77%

MATERIALS	
SHAFT	Duplex 2205 S31803 ASTM A276/479
SHELL	316 SS S31600 A312
SHELL BOLTING	316 SS S31600 A193/A320/F593
INLET/DISCHARGE	316 SS S31600 A351
IMPELLERS/DIFFUSERS	316L SS S31603 ASTM 276/479
MOTOR ADAPTER	Anodized 713 aluminum casting A07130 ASTM ZC81A
MOTOR COUPLING	Flexible disc coupling - FNC treated Carbon Steel S45C ASTM 1045
COUPLING GUARD	316L S31603 ASTM 276/479
PUMP LEVELING FOOT	Powder coated carbon steel A36 ASTM A570/A
MECHANICAL SEAL	316 Carbon silicon carbide Buna N FITS ISO DIN/ANSI TYPE 2100
BASEPLATE	Painted carbon steel A36 (optional) ASTM A570/A

OPTIONS	
Inlet placement available in 90° increments	
Passivated and Electropolished Impellers/Diffusers	

OUTLINE	
OUTLINE DIMENSIONS	Each MSB model is custom designed to specific customer requirements. Contact FEDCO for specific outline dimensions

FITTINGS	
PIPE JOINTS	Grooved-style couplings Inlet/Outlet 3"/3"
EYE BOLTS	Motor only

DRIVE	
MOTOR	Available per customer specific requirements NEMA FRAME STANDARD, IEC AVAILABLE

BEARINGS	
THRUST	FEDCO Water Bearing™ Product Lubricated
COOLING	Product provides cooling to all bearings
LUBRICATION	Product lubricated (no user lubrication required)

TESTING AND INSPECTION	
PERFORMANCE TEST **Hydraulic Institute (HI) Hydrostatic and Centrifugal Pump Testing Standards	Standard
HYDROSTATIC TEST **Hydraulic Institute (HI) Hydrostatic and Centrifugal Pump Testing Standards	Standard
VISUAL/DIMENSION CHECK	Optional
VIBRATION TEST (4.5mm/sec RMS (0.177"/sec))	Optional
WITNESS TEST	Optional
CERTIFIED TEST DATA	Optional
MATERIAL CERTIFICATES	Optional

SHIPPING	
PROTECTIVE COVERS	Standard
EXPORT CRATING	Standard
ADDITIONAL SHIPPING OPTIONS	Available per customer requirements
ESTIMATED UNIT WEIGHT	Contact FEDCO for specific design weight



NOTE: All numeric values are based on performance norms. Specific performance data is included with each individual unit. FEDCO reserves the right to make specification changes at any time without prior notice. email: sales@fedco-usa.com

**General Code Groups, Associations, Laboratories, and Approval Bodies include the American Society for Testing and Materials (ASTM), the International Organization for Standardization (ISO), and the NSF International. Please contact your FEDCO representative for any additional information.